Water & Sewage **Pumping and Treatment Engineers**  Amos Pumps (UK) Ltd Carminnow Ind. Est, Bodmin. PL31 1EP Tel: 01208-72613 Fax: 01208-77448

Amos Pumps (UK) Ltd Wendron, Helston, Cornwall. TR13 0PY Tel: 01326-573341 Fax: 01326-572322

## City JS & **Jet Stainless Steel Pumps**

\*\*\*\*\*\*\*\*\*\*\*\*Technical Data Sheet\*\*\*\*\*\*\*\*

### **General Characteristics**

These pumps are extremely reliable and economical being fitted with a well proved internal ejector inside the pump body. They have been used for many years to provide drinking water for homes, farms, nurseries and many industrial uses from springs and wells. The sturdy and compact design lends itself for many uses including the fitting of pressure vessels for automatic water distribution.

**Motors** - 240/220v, 1ph, 50Hz to IP44 protection, aluminium motor casing totally enclosed external fan cooled, induction motor with permanent-split capacitor.

0.5hp motor: JS 05 & Jet 05 0.8hp motor: JS 08 & Jet 08

1.0hp motor: JS 10H, JS10L, Jet 10H & Jet10L 1.2hp motor: JS12H, JS12L, Jet12H & Jet12L 1.5hp motor: JS15H, JS15L, Jet15H & Jet15L

### **Pumps**

Components common to both models:-Ejector unit & impeller - Noryl GFN2V Motor shaft - Stainless steel AISI 416 Mechanical seal - Ceramic and graphite Pump casing of Jet - Stainless steel **AISI 304** Pump casing of JS - Cast iron




JS Range



Jet Range

JS & Jet Nov 05





Amos Pumps (UK) Ltd Carminnow Ind. Est, Bodmin. PL31 1EP Tel: 01208-72613 Fax: 01208-77448 Amos Pumps (UK) Ltd Wendron, Helston, Cornwall. TR13 0PY Tel: 01326-573341 Fax: 01326-572322

# City JS & Jet Pressure Sets

#### **General Characteristic**

These compact pressure sets will increase the pressure of potable or clean water for many uses such as domestic or agricultural water supply, irrigation, car washing or connecting to industrial process machines after a type 'A' air gap has been generated. It's simple to install with only three connections, (plumbing water too and from the unit and making the electrical connection). The versatility and quietness of these units lends themselves to 1001 uses, all being economical to run and inexpensive buy.





City JS150 mounted above a 100 litre Horizont al pressure vessel.



City JS50 mounted above a 20 litre horizontal

### **Technical Specification**

These pumps are of the well proven Jet type with noryl impeller and diffuser inside the pump body, attached to a motor via a stainless steel drive shaft. A start capacitor is housed above the motor, cooling is by an external fan protected by a steel cover. Fitted onto the pump body are a pressure switch, preset to 20/40 lbs/sq./inch and a pressure gauge, these are connected with 2 metres of power cable. The pump is bolted above a horizontal surge tank having a removable butyl diaphragm. From the discharge of the pump is a three way tee and flexible hose, this transports water under pressure to the surge tank. Water connections too and from the pump are 1" B.S.P. female ports. The complete unit starts and stops automatically by sensing the pressure of water in the delivery pipe.

